



TECHNICAL DATA SHEET

TO LUBE 4410

Non-Ionic multipurpose polymeric lubricant which reduces abrasion and helps prevent creasing and running marks during wet processing / dyeing of fabric and garments. It is non foaming and also resistant to high temperatures, acids, alkalis and hard water salts.

PROPERTIES :

Appearance : Viscous Colourless liquid
Base : Blend of polymers and Amide condensate product
Ionic Nature : Non-Ionic
pH (1 % Soln) : Approx 6.50 {(+/-) 0.5}
Compatibility : Compatible with cationic, non ionic products and enzymes

APPLICATION:

Dosage : 0.5 to 1.0 gpl
Temperature : 30 to 60 Deg C
pH : 6.0 – 7.0

HANDLING & SAFETY:

Storage : To be kept away from direct exposure to sunlight
Safety : Refer MSDS
Packing : 50 Kg HDPE Carboys
Shelf Life : Twelve Months

*

** All information quoted above is based on our experience and actual know-how, but is given without guarantee and obligation. Recommendations on the applications and use of our products should be adapted to the particular user's conditions and other materials employed. Users are responsible for certification of use of their product and for complying with local legislation. Suggestions of use shall not be taken as inducements to infringe any patents or grant any license under a valid patent and are provided for illustrative purposes only.*

TFT BIOTECH INDIA PVT LTD

AP-297, 30th street, Kambar Colony, Anna Nagar West, Chennai-600040,
Tamilnadu, India

Ph- 91-44-26182557 / 26186079 Fax-91-44-26181364

Email: info@tftindia.com