



TECHNICAL DATA SHEET

TO LVL 6210

TO LVL 6210 is an excellent leveling agent which ensures that the dye is dispersed evenly through out the fabric providing uniform & level dyeing.

PROPERTIES :

Appearance : Yellow viscous liquid
Base : Aliphatic ethylene oxide condensate
Solubility : Soluble in water
pH : 6.5 – 7.5 (Of 10% Soln.)
Compatibility : Compatible with anions, cations & non ionic
Stability : Stable to acids, alkalis, salts and hard water

APPLICATION:

Dosage : 0.8 to 1.5 gpl
Temperature : 45 Deg C to 75 Deg C
pH : 7.0 – 10.0

HANDLING & SAFETY:

Storage : To be kept away from direct exposure to sunlight
Safety : Refer MSDS
Packing : 50 Kg HDPE Carboys
Shelf Life : Twelve Months from the date of manufacture

¹ All information quoted above is based on our experience and actual know-how, but is given without guarantee and obligation. Recommendations on the applications and use of our products should be adapted to the particular user's conditions and other materials employed. Users are responsible for certification of use of their product and for complying with local legislation. Suggestions of use shall not be taken as inducements to infringe any patents or grant any license under a valid patent and are provided for illustrative purposes only.

TFT BIOTECH INDIA PVT LTD

AP-297, 30th street, Kambar Colony, Anna Nagar West, Chennai-600040,
Tamilnadu, India

Ph- 91-44-26182557 / 26186079 Fax-91-44-26181364

Email: info@tftindia.com